



## **ASSEMBLY INSTRUCTIONS C8S, C8B, C8SB C81 AND C88 PRESSING TABLES**

If your table is produced *before* January 1, 2009 (please refer to the data label under the black metal box with the switches) please follow these instructions.

- Remove the ironing board cover.
- Using the bracket as a template, drill 5 holes of 3.5 mm at the base of the ironing board, at a distance of 20 cm from the steam station tray.
- Place the support bracket in the right position and screw in the 5 screws.
- Replace the cover on the board.
- Fix the bottle holder C8B with the washer and screw and fix the wand perpendicular to the bottle holder tube with washers and nuts, as indicated in the drawing.
- Fix the nut to the support using the screw and the washer; insert the rotating S-tube and finally the sleeve arm board in the tube.

If your table is produced *after* January 1, 2009 (please refer to the data label under the black metal box with the switches) please follow these instructions.

- Remove the ironing board cover and unscrew the 5 screws below the board.
- Place the support bracket in the right position and screw in the 5 screws.
- Replace the cover on the board.
- Fix the bottle holder C8B with the washer and screw and fix the wand perpendicular to the bottle holder tube with washers and nuts, as indicated in the drawing.
- Fix the nut to the support using the screw and the washer; insert the rotating S-tube and finally the sleeve arm board in the tube.

