

bernette Funlock Model	b42	b44	b48	b64
GENERAL MACHINE FEATURES				
Motor Type The bernette line offers machine horsepower options for all types of sewists from the crafter to the discerning stitcher.	AC	AC	AC	AC
Maximum Sewing Speed (stitches per minute) Count on efficient, reliable performance with a sewing speed up to 1,300 stitches per minute (SPM).	1,300 SPM	1,300 SPM	1,300 SPM	1300 SPM
Free Hand System with Knee Lifter Use the knee-operated lever to raise & lower the presser foot allowing your hands to manage your project at all times.				•
Electronic Foot Control/Power Cord The electronic foot control provides consistent needle penetration at any speed from slow to full; success is achieved with both intricate and assembly-line projects.	•	•	•	•
Freearm Freearm for easy sewing of tubular projects such as cuffs, legs and necklines.				•
Large Sewing Space More overlocking space to the right of the needles offers comfort and more maneuverability when stitching large and small projects. Allows for easy access to the needles with the right hand. Ideal for handling from the right when the left hand is holding fabric and notions in place over the freearm.				5″
Sewing Light An LED light illuminates the sewing and looper area making it easier to thread the needles and loopers as well as reducing eye strain while stitching projects in a brighter lit area.	2	2	2	5
Automatic Thread Tension Release As soon as the presser foot is lifted, the thread tension discs release automatically and allow easy threading.	•	•	•	•
Two-step Presser Foot Lifter The Two-step Presser Foot Lifter provides additional clearance under the foot when overlocking multiple layers or bulky fabrics. The Front Foot Lift gives an additional lift to the front of the presser foot enabling accurate positioning of multiple layers of fabric and bulky projects underneath it.	•	•	•	



bernette Funlock Model	b42	b44	b48	b64
Individual Thread Tensions Individually Adjustable Thread Tension for each needle and looper allow for perfecting stitches when using a variety of fabrics and threads. Use any combination of fabric and thread and have the ability to perfect and personalize the stitch beyond the pre-set limits.	•	•	•	•
Presser Foot Pressure Adjustment By simply turning an exterior knob, presser foot pressure is adjustable to accommodate sheer to thick fabrics.	7-Step	7-Step	7-Step	7-Step
Upper Knife Drive from Below Designed with the knife drive under the stitch plate, the sewing area around the needles and looper area is open for easier threading while providing accurately cut fabric edges.		•	•	•
Knife On/Off The Upper Knife is quickly released with the turn of a knob, lowering the knife when opting not to trim fabric.		•	•	•
Differential Feed Differential Feed ensures wave-free seams in knits and prevents puckering in fine fabrics, while allowing deliberate gathering as an option. With an easily accessible dial, adjustments to the fabric feed can be made even while sewing. Settings range from 0.6 to 2.0.	•	•	•	•
Thread Tension Infinitely variable and easily adjustable, the thread tension dials ensure quick and accurate set-up for all projects.	•	•	•	•
Micro Thread Control (mtc) With the Micro Thread Control, the over-edge thread length can be set directly resulting in the perfect seam with one quick adjustment.				•
Stitch Length With an infinitely variable, easily accessible, numbered dial on the exterior of the machine, stitch length can be adjusted to perfection – even while sewing.	1-4	1-4	1-4	1-5
Overlock Seam Width A range of seam widths determined by a combination of cutting width and needle position(s) assure successful seaming for all types of fabrics.		3-7	3-7	2.8-7.0
2.8 / 5.6 mm Coverstitch Width For a narrow coverstitch width of 2.8 mm, use the center needle and the right or left needle. For a wide coverstitch width of 5.6 mm, use all three needles, or the right and left needles only.	•		•	



bernette Funlock Model	b42	b44	b48	b64
3 - 10 mm Combo Stitch Width Create a 5-thread stitch utilizing the chainstitch and overlock stitch functions in one operation. This 10 mm wide stitch provides a professional finish to a secure seam.			•	
Built-in Rolled Hem Lever With the rolled hem lever built-into the stitch plate, it is easy to switch to a rolled-hem stitch and back again by simply moving the rolled hem lever – no need to change the stitch plate or presser foot.		•	•	•
Cut-offs Bin This standard accessory is easily attachable and catches threads and fabrics while overlocking.		•	•	•
THREADING FEATURES	b42	b44	b48	b64
Automatic Air Threader Conveniently push a button, the looper threads are automatically threaded.				•
Color-coded Threading Paths Color-coded threading paths, along with a threading diagram inside the looper cover, ensure accurate threading every time.	•	•	•	•
Lower Looper Threader Aide The Lower Looper Threader Aide helps in the quick threading of the lower looper.	•	•	•	•
Threading Chart A color-coded theading chart is located inside the threader cover.	•	•	•	•
Needle Pad A foam needle pad is in the base of the spool stand, right side, easy accessible for needles and pins.				•
Safety Switch An open looper cover activates the safety switch thus preventing the accidental operation of the overlocker during the threading process.	•	•	•	•



bernette Funlock Model	b42	b44	b48	b64
STITCH FEATURES				
Total Stitches	4	15	23	16
4-thread overlock stitch		•	•	•
3-thread super stretch		•	•	•
3-thread overlock (wide/narrow)		•	•	•
3-thread flatlock (wide/narrow)		•	•	•
3-thread narrow seam		•	•	•
3-thread rolled hem		•	•	•
2-thread wrapped overlock (wide/narrow)		•	•	•
2-thread flatlock (wide/narrow)		•	•	•
2-thread rolled hem		•	•	•
2-thread overlock stitch				
3-thread picotstitch				•
4-thread/3-needle coverstitch	•		•	
3-thread/2-needle coverstitch(wide/narrow)	•		•	
2-thread chain stitch	•		•	
4-thread safety stitch (2-thread overlock & chain-wide/narrow)			•	
5-thread safety stitch (3-thread overlock & chain-wide/narrow)			•	



bernette Funlock Model	b42	b44	b48	b64		
FEET AND BASIC ACCESSORIES						
Feet as Standard	Standard Coverstitch Presser Foot	Standard Overlock Presser Foot	Standard Overlock/ Coverstitch Presser Foot	Standard Overlock Presser Foot		
Upper Looper Converter		•	•	•		
Cover/Chainstitch Extension Plate			•			
Slide-on Table				•		
Accessory Box Plus accessory storage in looper cover	•	•	•	•		
Cut-offs Bin	•	•	•	•		
Dust Cover	•	•	•	•		
WARRANTY	5 years Mechanical; 1 year Electronic; 1 year Electrical					