


 NAOMOTO

HYS-520

**GRAVITY FEED
BOTTLE IRON**



**THE BEST JUST
GOT BETTER**

GRAVITY FEED BOTTLE IRON

HYS-520

NEW UNIQUE NON-STICK AND NO-RESISTANCE SOLE COATING.

DIRT AND FUSIBLE RESIN CAN BE WIPED OFF WITH JUST A CLOTH.

NO NEED FOR TEFLON SHOE

THE RESULT - EASIER AND FASTER IRONING

SPECIALLY DESIGNED FOR USE

in garment factories, laundry and dry cleaners, apparel and alteration stores, boutiques, department stores, hotels, hospitals, etc.

ELECTRONIC TEMPERATURE CONTROL

Naomoto's unique IC electronic temperature control (N-89S) has a precision and accuracy of +/-2°C (4°F).

FLUSH TEMPERATURE DIAL

Now the temperature control dial is flush with the surface of the rear plate. Finger light for temperature adjustment, the simple flush design prevents accidental movement of the dial.

EXCELLENT BALANCE

A combination of the latest technologies in design and synthetic materials produced an iron of superior balance. Low in height and weight, you can iron comfortably all day.

EASY CLEANING

A much bigger opening at the front makes easier access for cleaning the chamber. Special tool kit included.

MOLDED URETHANE HANDLE

The ergonomic molded urethane handle is designed to fit the human hand. Urethane material has natural insulation properties for operator comfort.

OPEN END HANDLE

The open end design gives excellent visibility for ironing into tight areas, inside cuffs or pockets, etc.

LIGHT TOUCH SWITCH

Minimum pressure from thumb activates switch for instant steam flow.


NO MORE STEAM LEAKS:

Now, the chamber and sole is one piece, which eliminates potential steam leaks between the chamber and the base. In turn, this will eliminate any heating element failure due to steam/water leakage.

HEAT SHIELD

Improved non-woven Nomex material protects the hand from heat up to 280°C.

Model	HYS-520
Weight	2 kgs
Electrical	110/220V,880W
Sole finishing	Hard nickel+Teflon



*Specifications are subject to change without notice.



19-8, Ishigatsuji-cho, Tennoji-ku, Osaka 543-0031, Japan
Tel 06-775-2506, Fax 06-775-2511
E-Mail:naomoto@alpha-web.or.jp