

# Easy to use even for beginners! Overlock Sewing Machine.



### Adjustable Differential Feed

is easily controlled and adjusted by a dial located on the exterior, left hand side of the machine.



### **Automatic Lower Looper Threading**



allows for easy threading in seconds- simply push the automatic threader up and then thread goes through automatically.

### Adjustable Lower Knife



adjusts the lower knife quickly to change the width of fabric in the seam allowance, for perfect seams and rolled edges.

# Adjustable Stitch Length



turn dial is located on the exterior right hand side within the range of 1 to 4 mm.

### Standard Specifications

Sewing Speed	1,300 spm
Number of Threads	3/4 Threads
Needle	ELX705
Standard Overlock Width	Left Needle: 6mm Right Needle: 4mm Rolled Hem: 2mm
Stitch Length	1-4mm(Standard: 2.5mm)
Differential Feed	0.8-2.0 Ratio
Built-in Rolled Hemming	Right Needle/3 Thread
Decorative Flatlock	Right or Left Needle/3 Threads
Presser Foot Lift	max 6mm
Dimensions	292mm(w)×295mm(d)×290mm(h
Weight	7.4kg

# JUKI CORPORATION 2-11-1,TSURUMAKI, TAMA-SHI, TOKYO, 206-8551, JAPAN



## **Automatic Rolled Hemming**

can now be created quickly and easily with built-in fingertip control. There is no need to change the foot or plate.



**■**Overlock SCHOOL STATE OF THE STATE OF TH



# Retractable Upper Knife



removes the upper knife so that threading is made safer and easier.

### Lay-in Type Thread Tension Slots



throughout the machine make threading easy and efficient.





#### Optional Attachments

Elasticator Foot Part No. 40131947









Gathering Foot Part No. 40131948 Piping Foot Part No. 40131950





MO-50e

