## Thank you for your purchase of the Arrow 601/611 White Sewing Table.

If you have questions on how your table works, missing or damaged parts please call our toll-free line at **1-800-533-7347** or **cs@arrowcabinets.com our website is www.arrowcabinets.com.** A customer service representative is available Monday through Friday 8:00 AM till 5:00 PM Central Standard Time.

## **How to Adjust Your Sewing Surface for the Flatbed Position:**

- 1. Push the quick lift lever down and push the sewing surface or platform down into the lower position known as the flatbed position.
- 2. Place your sewing machine on the platform, while platform is in the flatbed position.
- 3. The ideal flatbed position should allow your sewing machine's needle tip to be level with the edge of the table. If your needle tip is level, you will not need to adjust the platform height.
- 4. If your sewing machine's needle tip is sitting lower then the edge of the table:
  - a. Remove sewing machine from table
  - b. Pull quick lift lever back up and lock the platform in the top position.
  - c. Begin to tighten the bolt on the Eye-Hook until you achieve the proper flatbed height for your sewing machine. (note you may need to adjust this position several times before finding the correct bolt tightening position)
- 5. If your sewing machine's needle tip is sitting above the edge of the table:
  - a. Follow the same steps in step 4 accept for step C: Instead loosen the bolt on the Eye-Hook.
- 6. If after completing these steps your sewing machine's sewing surface is not level you may need to shorten the chain for shorter machines by moving the screw or call us for an additional length of chain for taller machines.
- 7. Remember to lock the legs before using the table. Place peg in rubber stopper.
- 8. When moving platform from flatbed to top position by pulling up on the quick release lever, remove your sewing machine from platform.



Machine in Flatbed

**Bolt on Eye-Hook** 

**Adjustable Chain Links** 

Leg Locking Stopper

Note: Table should only be moved after the machine is removed and the legs are properly folded up. Also, do not raise or lower the platform with the machine on it.

Also see our video of how to use the Gidget table at: http://www.arrowcabinets.com/videos.php