



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 077-004
Product name Industrial Silicone Release Agent
Effective date 03-Mar-2011
Company information Sprayway, Inc.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 07
Supersedes date 13-Aug-2010

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE
Aerosol. Will be easily ignited by heat, spark or flames. CONTENTS UNDER PRESSURE.
Harmful in contact with eyes. Irritating to skin. Irritating to respiratory system. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Inhalation. Eye contact. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Irritating to skin.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	20 - 30
Propane	74-98-6	20 - 30
n-Butane	106-97-8	20 - 30
Aliphatic Petroleum Solvent	64742-89-8	10 - 15
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	5 - 8
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops and persists.
Inhalation	Move to fresh air. For breathing difficulties, oxygen may be necessary. Call a physician if symptoms develop or persist.
Ingestion	Call a physician immediately. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Notes to physician	Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Alcohol foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Do not get in eyes.
------------------------------	---------------------

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	82.4 °F (27.8 °C) estimated
Color	Colorless.
Density	0.6445 g/cm ³ estimated
Flammability (HOC)	37.0038 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	50 - 70 psig @ 70F
Solubility	Negligible
Specific gravity	0.6446 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects Acute LD50: 8679 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
Aliphatic Petroleum Solvent	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

12. Ecological Information

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

LC50 715 mg/L estimated, Fish, 96.00 Hours,
EC50 44905 mg/L estimated, Daphnia, 48.00 Hours,
IC50 31339 mg/L estimated, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Aliphatic Petroleum Solvent	64742-89-8	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

MSDS sections updated

Product and Company Identification: Product and Company Identification
Composition / Information on Ingredients: Ingredients

Prepared by

Regulatory Compliance